

Instrument Solutions DATASHEET Quality products from leading manufacturers





Pegasor AQ[™] Indoor



Pegasor AQ[™] Indoor

Accurate feedback on indoor air quality

What are we breathing

PM2.5 pollution is a well-known problem and monitoring PM2.5 concentration is a must. However, traditional PM2.5 monitoring methods are not sensitive to the most harmful, ultrafine particles, diameter below 0.1 micrometers. All Pegasor instruments are capable to detect particles larger than 0,01 um and thus measure also the most dangerous particles.



Technical specification

Sensor type	Diffusion charging operating principle
Measuring range	0.001 - 200 mg/ m ³
Maximum responsive particle size	0.01 - 2.5 µm
Particle size cutter	PM _{2.5}
Sampling mode	Built in suction pump
Flow rate	3 L/min
Resolution	0.001 mg/m ³ (with 1 min integration time) 0.1% of reading
Sampling rate	1/sec
Operation interface	4,3" Color display touch screen
Time constant	1-300 s adjustable by user
Battery operation time	10h - 24h -100h (depending of the sampling rate)
Battery type	Li-ion
AC power supply	External power supply, 100 – 240 VAC, 50/60 Hz
Operating temperature range	0 - 50 °C
Storage temperature range	-20 – 60 °C
Communication interface	Ethernet with Modbus protocol, optionally wireless (3G/4G modem)
Automatic zero setting function	Yes
Document printer	Yes, with optional device
Service period	12 months, depending environment
Configurable to PM, PN or PA measurements	Yes
Temperature and relative humidity measurements	Yes, with Vaisala HUMICAP [*] sensor
${\rm CO}_{\rm 2}$ concentration measurement	Yes, with Vaisala CARBOCAP' sensor
Analog output mode	0 -10 V or 4 - 20 mA
Analog output range	Adjustable by user
Alarm output	Yes, for different alarms
Alarm setting point range	Adjustable
Built-in data storage	1 GB
Data storage type	Flash memory
Storage interval	1s - 1h
Maximum data points	> 1,000,000
Software	Pegasor
Dimensions (wxhxl)	150 x 200 x 300mm
Weight	< 1.5 kg
Weight GPS for location indicator	< 1.5 kg Yes, optional

Connections

USB in, USB out	Yes
Bluetooth	Yes
WLAN	Yes, optional
Ethernet	Yes
3G/4G	Yes, optional
Analog (V and mA)	Yes

Reliable Pegasor technology

Pegasor instruments electrically charge all particles entering the device and measure the electrical current carried by particles. The measurement result can be shown as particle mass concentration (PM2.5), particle number concentration (PN) or active particle surface area concentration (PA). Pegasor products have extraordinary stability, low maintenance need and long measurement periods.

Pegasor AQ[™] Indoor

Pegasor indoor measuring instrument is a perfect tool for all public and private places where real time monitoring of living environment with data storage is needed.

KEY FEATURES:

- Measures ultrafine particles
- Detects temperature, relative humidity and CO2 concentration
- Self diagnostic procedure guarantees accurate continuous measurements
- Fits easily to any indoor environment
- Measured data can be read from the touch screen in graphical and numerical form
- Measured data can be stored on hard disk or USB and transferred to data storage, cloud service, or printed out as separate document
- Easy maintenance and long maintenance interval
- Reasonable pricing and very low cost of ownership

Applications

Pegasor data can be used for ventilation system and filtration efficiency monitoring, and indoor air quality classification.



Pegasor provides unique fine particle sensor products. Our products are based on diffusion charging of particles, technology capable of covering all fine particle monitoring applications, such as ambient and indoor air quality monitoring and emission measurements. Same measurement principle makes all measurements comparable. This is a key feature in combining measurements from different spots into wider information base.

Our technology and sensors are a result of acknowledged and solid scientific research, as well as extensive track record of industrial fine particle measurements. Our products are available throughout Asia, Europe and North America through via comprehensive network of local distributors and leading manufacturer partners.

Headquarters

Hatanpään valtatie 34 C FI-33100 Tampere Finland Available from : BSRIA Instrument Solutions Tel No. 01344 459314

Tel. +358 (0)10 423 7370 E-mail: info@pegasor.fi



Instrument Solutions: Quality products from leading manufacturers

Hire

BSRIA Instrument Solutions offer an extensive range of quality test and measurement instrumentation for you to hire. The widest range and in-depth stocks of the latest equipment are available at competitive prices. BSRIA Instruments Solutions has built its fine reputation by providing the most reliable and advanced equipment from the leading manufacturers and supporting it with a high level of customer service and technical support to meet with your requirements and expectations.

- Fast delivery: next day or same day delivery available
- Flexible terms: short and long term hire contracts
- Latest technology: new models added to stock regularly

E: hire@bsria.co.uk

Sales

BSRIA Instruments Solutions specialises in providing test and measurement products in many fields of measurement, especially in the building services sector. Appointed as an official distributor for over 25 of the leading manufacturers in the test and measurement instrumentation market, we are able to offer a choice of the best instruments available to reach your requirements.

- Call for a competitive quote
- Many instruments available ex-stock
- In-house calibration options available on most instruments
- On-line purchasing available for many products on our website

E: instruments@bsria.co.uk

Calibration

The ISO and UKAS accredited calibration department within BSRIA Instrument Solutions draws upon many years of BSRIA's experience in the building services industry. This unparalleled knowledge of the measurement and instrumentation requirements of the services industry gives the calibration department a unique advantage to meet your calibration needs.

- Fast service: 5 days standard turnaround
- 24 hours and while-you-wait services available on request
- Custom calibration points
- For a full scope of calibration please call

E: calibration@bsria.co.uk

and performance

BSRIA head office Bracknell

Calibration laboratories and offices in the South and North:

Old Bracknell Lane West, Bracknell, Berkshire RG12 7AH

BSRIA North Preston

68 Walton Summit Road, Walton Summit Centre, Bamber Bridge, Preston, Lancashire PR5 8AQ



W: www.bsria.co.uk/instruments T: 0800 254 5566 (UK Free) T: +44 (0)1344 459 314



Improving the built environment

Delivering knowledge

Measuring compliance